

STANDARD



**Loop**  
steel, nickel-plated. Aperture  
approx. 24 mm wide



Tried and tested  
up to 1.3 times the  
weighing range Max

Price reduction

**Back-lit  
LCD display**  
digit height  
23 mm

OPTION  
**DKD**  
Certificate  
+5 days



**Tare:**  
put back displayed value to  
"0" during weighing process.  
Now removed or added  
loads are directly displayed

**Adjustment  
program CAL**  
external test weights  
additional price

**Data hold function**  
the display is "frozen" via  
the HOLD-key until any key  
is pressed again

**Integrated  
rechargeable  
battery pack**  
standard, operating time  
approx. 120 h. Charging  
time approx. 8 h with mains  
adapter

**Casing**  
WxDxH 150x140x155mm,  
total height from loop to  
hook 360 mm  
(HUS 600: 380 mm)

**Charge display**  
for integrated rechargeable  
battery pack visual via LED

**Hook**  
with safety catch. Steel,  
nickel-plated, turnable.  
Aperture approx. 20 mm  
(HUS 600 ca. 24 mm)

**Infrared  
remote control**  
standard.  
Range approx. 2,5 m.  
All functions are  
selectable. WxDxH  
120x60x15 mm

**Ready for use**  
batteries size AAA  
(2x 1,5 V) included

Model	Read- out d g	Weighing range Max kg
KERN		
HUS 60K20	20	60
HUS 150K50	50	150
HUS 300K100	100	300
HUS 600K200	200	600

Precision 0.2% of Max. Net weight approx. 4 kg.  
Permissible humidity: max 85%, not condensing.

